

# OSA 3200

## Optical pumping cesium clock



Science



Metrology



Research



Ground station



Time scale

## Benefits

- Unique innovation**  
First commercial cesium atomic clock utilizing optical pumping technology
- Compact and modern design**  
Features an intuitive LCD touch screen and Ethernet connectivity for simplified local and remote configuration
- Proven physics**  
Builds on and improves widely deployed magnetic cesium atomic clock technology
- Technology leadership**  
Developed by the only company with deep expertise in both synchronization and photonic solutions, pioneering optical pumping cesium technology
- RoHS-compliant**  
Fully compliant with the latest RoHS standards, meeting strict EU demands
- Secure and remote management**  
Featuring SSH, SNMPv3 support, fully integrated with Adtran's Mosaic Network Controller management system for enhanced security
- Comprehensive logging**  
Includes syslog, alarm log, audit log and security log for full operational visibility

## Overview

**In critical applications such as metrology labs, ground stations, satellite navigation and communication, and timekeeping systems, an ultra-stable and precise frequency source is essential to ensure reliable performance.**

The OSA 3200 SP is the industry's first commercial optical cesium atomic clock. Engineered for demanding environments, it provides highly precise synchronization, making it ideal for metrology institutes, mission-critical networks and defense operations.

With its uniquely compact design, the OSA 3200 SP offers a combination of features and performance unmatched in the market. Equipped with a long-life cesium tube, it meets long-term operational demands where sustained accuracy is critical. The OSA 3200 SP provides a highly stable and accurate frequency source with an accuracy better than  $\pm 1 \times 10^{-12}$  Hz and excellent frequency stability.

Compact and portable, the OSA 3200 SP is well suited for space-constrained environments while maintaining exceptional stability.



Front view

Metrology cesium clock

Rear view

# OSA 3200

---

## High-level technical specifications

### Optical pumping benefits

- No magnetic selection; optical preparation of atoms instead
- 100 times higher Atoms flux
- Simpler mechanical design
- Higher product reliability

### Longest lifetime

- Optical cesium has much higher efficiency in utilizing cesium atoms
- No compromise between lifetime and performance

### Highest accuracy

- Superior short-term and long-term stability compared to magnetic cesium clocks
- Tenfold Stability improvement over 10 years

### Robust design

- Building on our longstanding and field-proven competence with magnetic clock and photonic technology
- Reusing unique cesium tube assembly competence
- Operating critical components outside vacuum tube

### Modular design

- 3RU 19" rack-mounting shelf
- Hot-swappable power supplies and battery modules
- Wide range of synchronization input and ultra-low noise output interfaces

### Common management

- Easy to use with automated startup and an intuitive menu with touch screen
- Remote (IP) and local (RS232) management via Windows GUI
- Simple integration with any host infrastructure
- SSH
- Syslog, alarm log, audit log, security log and clock data

## Applications in your network

### Metrology, time keeping institutes and science labs

- Provides highly stable, low-noise frequency outputs for precise measurements

### Defense communication and space navigation

- Delivers superior short-term stability to enhance navigation precision
- Offers longer holdover for frequency and timekeeping, ensuring consistent long-term performance
- Produces ultra-stable carrier frequencies with low phase noise, optimizing communication systems for critical application

# OSA 3200

## Product specifications

### Frequency accuracy

- Frequency accuracy:  $\leq \pm 1 \times 10^{-12}$
- Frequency reproducibility after power cycle  $\leq \pm 1 \times 10^{-13}$

### Frequency offset adjustments

- Resolution:  $\pm 1 \times 10^{-15}$
- Range:  $\pm 1 \times 10^{-9}$

### Frequency stability versus magnetic field

- Versus  $\pm 1$  Gauss:  $\leq \pm 10^{-13}$

### Short-term stability (frequency outputs), Allan Deviation

Tau(T)	SP
1s	$\leq 1.2 \times 10^{-11}$
10s	$\leq 8.5 \times 10^{-12}$
100s	$\leq 2.7 \times 10^{-12}$
1000s	$\leq 8.5 \times 10^{-13}$
10,000s	$\leq 2.7 \times 10^{-13}$
100,000s	$\leq 8.5 \times 10^{-14}$
10 days	$\leq 5.0 \times 10^{-14}$
30 days	$\leq 5.0 \times 10^{-14}$
Floor (guaranteed)	$\leq 5.0 \times 10^{-14}$
Floor (Typical)	$\leq 4.0 \times 10^{-14}$

### Low noise frequency outputs

- Number of 10MHz outputs: 2
- Number of 5MHz outputs: 1
- Number of 100 MHz output: 1
- Signal format: sine wave
- Connector: SMA/F
- Load impedance: 50Ω
- Amplitude: 13dBm  $\pm 1$ dBm
- Harmonics:  $\leq -40$ dBc
- Non-harmonics (spurious)  $\leq -80$ dBc
- Isolation between outputs:  $-110$ dB

SBB phase noise	5MHz output	10MHz output	100MHz output
1Hz	$-106$ dBc/Hz	$-100$ dBc/Hz	$-70$ dBc/Hz
10Hz	$-136$ dBc/Hz	$-130$ dBc/Hz	$-90$ dBc/Hz
100Hz	$-145$ dBc/Hz	$-145$ dBc/Hz	$-105$ dBc/Hz
1,000Hz	$-150$ dBc/Hz	$-150$ dBc/Hz	$-115$ dBc/Hz
10,000Hz	$-154$ dBc/Hz	$-154$ dBc/Hz	$-120$ dBc/Hz
Floor	$-154$ dBc/Hz	$-154$ dBc/Hz	$-120$ dBc/Hz

### Timing digital outputs

- Number of 1PPS outputs: 4
- Frequency: 1 Hz
- Connector: BNC/F
- Signal format: pulse LVCMOS
- Load impedance: 50Ω
- Amplitude: 2.5Vpp with 50Ω load
- Jitter  $\leq 1$ ns RMS
- Rising edge  $\leq 5$ ns (10% to 90%)
- Output shape pulse
- Output timing signal significant slope: positive
- Pulse width: 100μs (adjustable)

### Synchronization input

- Number of 1PPS input: 1
- Frequency: 1 Hz
- Connector: BNC/F
- Signal format: pulse LVCMOS
- Load impedance: 50Ω or 1MΩ (programmable)
- Amplitude: min. 2.5V; max. 5V
- Pulse width: 100ns-100μs
- Input timing signal significant slope: positive or negative (programmable)

### Synchronisation of 1PPS timing outputs

- Synchronisation range:  $\pm 500$ μs
- One shot external sync resolution (sync on 1PPS Input)  $\leq \pm 10$  ns
- Manual phase adjustment of 1PPS outputs
- 4 outputs adjustable independently
- Resolution of manual adjustment: 1 ns

# OSA 3200

## Power supply and battery options

- Number of power supply modules: 2
- Redundant and hot swappable
- Automatic switching
- Option 1
  - AC 110–240V, C15 connector
  - Range 88V up to 264V
  - Range 45Hz up to 65Hz
- Option 2
  - DC +24V (range 18V up to 30V)
- Option 3
  - DC -48V (accepted range -36V up to -72V)
- Power consumption steady state at 25°C ≤50W
- Power consumption at warm-up ≤90W
- Battery option: 60 minutes operation (full charge)
- Charge time from empty load: 4 hours

## Environment and compliance

- Operating temperature: 10°C to +50°C
- Non operating temperature: -40°C to +70°C
- Operating relative humidity: 10% – 90% non condensing
- Vibration/Stationary – IEC 60068-2
- Basis ETSI EN 300019-2-3:2015 Stationary use Test specification T3.2 Environmental Class 3.2
- Random Vibration / Storage / Transportation / Drop
  - IEC 60068-2
  - Basis ETSI EN 300019-2 Storage Test specification T1.1 Environmental Class 1.1
  - Basis ETSI EN 300019-2 Transportation Test specification T2.2 Environmental Class 2.2
- Altitude: 0 to 15,000m
- Safety: IEC 62368-1, IEC 60825-1
- EMC and ESD:
  - EN 55032, CISPR 32, 47 CFR, Part 15, Sub part B
  - ICES – 003 Issue 7
  - EN 55035, CISPR 35,
  - EN 61326-1, IEC 61326-1
  - CE & UL compliant

Note: Certificate (EMC) updates in progress

- RoHS 10/10
- Comply with Directive 2011/65/EU of the European Parliament and Commission Delegated Directive (EU) 2015/863

## Mechanical

- Table top
- 19" rack mountable, 19" 3RU
- Width/with rack ears: 450mm/482.6 mm
- Depth: 510mm
- Height: 132mm
- Weight: 22Kg (with battery, 17 without)

## Management features

- Status LED
  - 3 LEDs on front panel
  - Type: Alarm, status, power
- Alarm relay
  - Maximum rating: U= 50VDC, I = 250mA
  - Connector: SUB-D 9/F
- Graphical touch screen display
  - Management functions
  - Alarm and status
  - Monitoring
  - Parameter setting
- Local management port
  - Connector: SUB-D9/M
  - Port configuration: 115200bps, 8bits, 1 stop bit
  - Management commands: CLI
  - Management software: Windows GUI
- Remote management port
  - Remote management port: Ethernet – TCP-IP
  - Connector: RJ45
  - Management commands: SNMP v3 (including authentication and encryption)
  - SSH
  - Management software: Mosaic Network Controller
- System logging
  - Configurable system timing source – local/NTP/SNTP
  - User configurable time zone and daylight saving time (DST)
  - SSH
  - Syslog, alarm log, audit log, security log and clock data

Updated June 10, 2025

